

Accessory

for ERHARD Diaphragm Valves with piston actuator

Positioner for Diaphragm Valves with piston actuator


Application

Pneumatic or electropneumatic positioners are proportional controllers, suitable for mounting onto single and double acting piston actuators. Independent of disturbing influences as well as frictional and medium forces, precise control is ensured.

Standard designs:	Pneumatic operating signal	0.2-1 bar
	Electric operating signal	0-20 mA
	or	4-20 mA
	Supply air pressure max.	4 bars
	Internal thread connection	R1/8

Double acting piston actuator, double acting positioner.

Single acting piston actuator with opening or closing spring, single acting positioner.



Additional equipment:

Power amplifier (internal thread connection 1/4 - NPT)

Pressure gauge for indicating supply pressures¹⁾

Integrated inductive (or pneumatic)¹⁾ limit signal transmitter

Explosion-proof design (Ex) EEx ib IIC T6²⁾

Cutting ring screwed connection R 1/8 on tube 6x1 mm

Cutting ring screwed connection 1/4 - NPT on tube 6x1/10x1 mm

¹⁾ For pneumatic positioner only.

²⁾ For electropneumatic positioner only.

Note: When placing the enquiry or order, please specify:

Kind of positioner (pneumatic, electropneumatic).

Required additional equipment.

General note:

Further details concerning additional units or additional equipment, connection possibilities, and further required accessory on request.